# P-UDDIGITAL COLOR PHOTO PRINTER





### Superb Photo Quality Prints In A Matter Of Seconds With A Low Operating Cost.

#### **KEY FEATURES**

- Adaptive thermal head management engine
- Ultra-fast, large volume printer
- High resolution photo quality prints
- Jam-free, roll-type mechanism
- Edge-to-edge printing
- Easy-to-use, convenient front access with paper catch tray
- High-speed USB 2.0

Mitsubishi's high-speed, high-volume CP-9550DW defines the new standard for digital photo printers delivering outstanding print quality at a low cost. The CP-9550DW delivers bright, bold colors and achieves an unparalleled level of consistency and accuracy. With the CP-9550DW, Mitsubishi unveils innovative and performance enhancing dual line technology and an adaptive thermal head management engine to improve head resolution which results in even greater image quality, detail and texture at superior resolutions. Incorporating a unique roll-type mechanism for jam-free reliability, the CP-9550DW will provide continuous high quality performance. For greater versatility, the CP-9550DW offers five different output sizes with edge-to-edge printing. Combining the utmost in image quality along with ultra-high speed, large volume printing and low-maintenance, the CP-9550DW will increase your business and provide an immediate return on investment.

# DIGITAL COLOR PHOTO PRINTER



#### **SUPERB PRINT QUALITY**

### Unique color imaging control system for superb image quality print after print.

- A unique color reproduction system developed specifically for the CP-9550DW delivers consistent print quality, regardless of ink sheet, for superb quality every shot.
- A revolutionary new system, the ink sheet rolls feature built-in Color Imaging Chips that contain specific data about the media. The printer uses this information to accurately control color characteristics.
- The CP-9550DW features an all-new 346 dpi thermal head for longer service life and improved print quality.

#### INNOVATIVE ENGINEERING New Advancements For Even Greater Printer Performance

- With optimized adaptive thermal head management engine pulse control, a key technology for dye sublimation printers, and internal 16-bit processing, the CP-9550DW delivers exceptionally accurate and detailed reproduction. Super-fast printing (15 seconds for 3.5 x 5" size) is yet another breakthough.
- Dual line heads improve head resolution and results in superb images with even greater detail and texture

#### **HIGH-SPEED**

#### **Exceptionally Fast, High Volume Printing.**

- A new feed mechanism combined with a simplified paper path delivers photographic prints at an exceptional speed.
- Equipped with two 32MB memory frames. Images can be stored in memory while printing.

#### **USER-FRIENDLY OPERATION**

#### Easy-to-use, convenient front access.

- The easy-access front panel simplifies paper loading and maintenance and includes a paper catch tray with a maximum recommended capacity of 20 prints.
- The color image control system monitors the number of prints remaining.
- High-speed USB 2.0 interface.

## SPECIFICATIONS Print Method Dye sublimation thermal transfer Resolution 346 dpi (Fine mode) Printing Performance Imaging area Fin 3 Fy Fr" 1240

Printing Performance	Imaging area	Fine mode	Super fine mode
	3.5 x 5"	1240 x 1812 dots	2480 x 1812 dots
	4 x 6"	1416 x 2152 dots	2832 x 2152 dots
	5 x 7"	1812 x 2452 dots	1812 x 4904 dots
	6 x 9"	2152 x 3146 dots	2152 x 6292 dots
Paper Size	3.5 x 5" (89 x 127 mm)		
	4 x 6" (102 x 152 mm)		
	5 x 7" (127 x 178 mm)		
	6 x 8" (152 x 203 mm) 6 x 9" (152 x 229 mm)		
		,	
Printing Time	3.5 x 5": approx. 15 sec; 4 x 6": approx. 16 sec;		
	5 x 7": approx. 25 sec; 6 x 8": approx. 32 sec; 6 x 9": approx. 33 sec		
Printing Area	Edge-to-edge		
Buffer Memory	32 MB (2 Frame)		
Interface	USB 2.0		
Driver Software	Windows XP/2000/ME/98; Macintosh OS X 10.3.3 (available via download only); Window Developers USB DLL available upon request		
Dimensions (W x H x D)	11.8 x 12.8 x 14.3" (300 x 325 x 365 mm)		
Weight	Approx. 37.4 lbs. (17Kg)		
Power Supply	AC 120V 50/60Hz, AC220-240V 50/60Hz		
Compliance	UL60950-1/TUV-GS, CE(LVD)		
Warranty	1 year parts and labor, 12 months or 20,000 prints which ever comes first on thermal head		

#### MEDIA PAPER OPTIONS Model Print Quantity Image Size CK9035 680 prints 3.5 x 5" (89 x 127 mm) CK9046 600 prints 4 x 6" (102 x 152 mm) CK9046PST (Back print postcard) 600 prints 4 x 6" (102 x 152 mm) CK9057 350 prints 5 x 7" (127 x 178 mm) CK9069 270 prints 6 x 9" (152 x 229 mm)

#### **REAR PANEL**



- 1. Mode switch
- 2. USB connection
- 3. AC input
- **4.** Fan



©2008 Mitsubishi Digital Electronics America, Inc. Standard features, options and specifications subject to change without notice. Microsoft, Windows and the Windows logo are registered trademarks of the Microsoft Corporation. All trademarks or registered trademarks are the property of their respective holders.

### Mitsubishi Digital Electronics America, Inc.

Imaging Products Division 9351 Jeronimo Road, Irvine, CA 92618 Toll Free: 888-307-0388 ipdinfo@mdea.com Technical Support: Toll Free: 888-307-0309 Email: tsupport@mdea.com

#### Canada:

Mitsubishi Electric Sales Canada Inc. Information Technologies Group Markham, Ontario 905-475-7728

www.MitsubishiElectric.ca

www.mitsubishi-imaging.com/photo